MATERIAL SAFETY DATA SHEET

1. Identification:

1.1. **The product name: WOOD OIL** wood preservative

Product identification code: PO

1.2. Manufacturer and marketing

AMELLO GROUP OÜ

Street: Laki 14 A City: Tallinn 10621 State: Estonia Tel: +372 6 720 471

Fax: +372 6 720 455 **E-mail:info@amello.ee**

1.3. **Emergency phone nr:**

UK- National Poisons Information Service Phone: 44 / 191 22 5135

B- Centre Antipoisons Ph: 070 / 245.245

2. Composition:

2.1. Classification: linseed oil product

2.2. Components:

CAS - NR	Component	Containing	Danger symbol
8001-26-1	Linseed oil	40-60 %	-
8001-20-5	Tung oil	30-50 %	
	_		

3. Hazard identification

3.1. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt with accordingly, e.g. by burning them.

4. First Aid:

- 4.1. Inhalation: ---
- 4.2. Skin contact: Wash off with soap and plenty of water.
- 4.3. Eye contact: Rinse immediately with plenty of water for at least 15 minutes. Get medical attention if necessary.
- 4.4. Ingestion: Rinse mouth and drink water or milk. Get medical attention if necessary.

5. Instructions concerning fire risk:

5.1. Put out the fire with a foam, powder or carbon dioxide (CO2) fire-extinguisher

6. Instructions concerning environmental risk:

- 6.1. Do not pour on ground or into sewerage
- 6.2. Cleaning: let it absorb into peat or sawdust and collect all waste.
- 6.3. Personal precautions: see item 8.

7. Handling and storage:

- 7.1. Handling
 - 7.1.1. Ensure adequate ventilation
 - 7.1.2. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt with accordingly, e.g. by burning them.
- 7.2. Storage: well ventilated and dry storage

8. Exposure controls / Personal protection:

- 8.1. Ensure adequate ventilation
- 8.2. Eye protection:---
- 8.3. Skin and body protection: ---
- 8.4. Hand protection: rubber gloves
- 8.5. Respiratory protection:---

9. Physical and chemical properties

- 9.1. Appearance, colour, odour: yellowish transparent liquid
- 9.2. Boiling point/range: ---
- 9.3. Flash point: ---
- 9.4. Inflammability: 260 °C
- 9.5. Explosion limits:---
- 9.6. Density: 0.93
- 9.7. Vapour pressure: ---
- 9.8. Water solubility: insoluble
- 9.9. Fat solubility: soluble

10. Stability and reactivity:

- 10.1. at normal conditions the liquid is stable.
- 10.2. If the oil is infiltrated into porous material: Danger of self-ignition.

11.Health

- 11.2 acute toxic: ---
- 11.3 irritating, corrosive: If the person is sensitive, it may cause skin irritation.
- 11.4 allergy: ---
- 11.5 inhalation: ---.

12.Environment

12.1 Biodegradable

13. Waste management

- 13.1 Collect all waste and destroy according to waste management program. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt accordingly, e.g. storing in the water or by burning them.
- 13.2 Empty and dry packages can be taken into the waste or disposed according to local legislation.

14.Transport

```
UN number ---
Land : ---
Sea ( IMDG) : ---
```

15. Regulatory information

```
Labelling: ---
R -PHRASES
---
S - PHRASES
```

16.Other information

- 16.1Uses or/and applications: wood care.
- 16.2 Exact operating instruction is on the label and on product instruction.