

PRODUCT SPECIFICATION

1. Identification:

1.1. **The product name:** Linseedoil – wood care

Product identification code: LO

1.2. **Manufacturer and marketing**

AMELLO GROUP

Street: Laki 14 A

City: Tallinn 10621

State: Estonia

Tel: +372 6 720 471

Fax: +372 6 720 455

E-mail:info@amello.ee

1.3. **Emergency phone nr:**

UK- National Poisons Information Service Phone: 44 / 191
22 5135

B- Centre Antipoisons Ph: 070 / 245.245

2. Composition:

2.1. **Classification:** linseed oil product

2.2. **Components:**

CAS - NR	Component	Containing	Danger symbol
8001-26-1	Cold pressed Linseed oil	100,00%	-

3. Hazard identification:

3.1. Repeated exposure may cause skin allergy. Irritative to eyes and skin.

3.2. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt with accordingly, e.g. by burning them.

4. First Aid:

4.1. Inhalation:

4.2. Skin contact: Wash off with soap and plenty of water.

4.3. Eye contact:

4.4. Ingestion:

5. Instructions concerning fire risk:

5.1. Put out the fire with a foam, powder or carbon dioxide (CO₂) fire-extinguisher

6. Instructions concerning environment risk:

6.1. Do not pour on ground or into sewerage

6.2. Cleaning: let it absorb into peat or sawdust and collect all waste.

6.3. Personal precautions: see item 8.

7. Handling and storage:

7.1. Handling

7.1.1. ensure adequate ventilation

7.1.2. do not smoke

7.1.3. keep containers tightly closed

7.1.4. obstruct the sparks of statical electricity

7.1.5. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt with accordingly, e.g. by burning them.

7.2. Storage: well ventilated and dry storage

8. Exposure controls / Personal protection:

8.1. Ensure adequate ventilation

8.2. Eye protection: ---

8.3. Skin and body protection: protective gloves

8.4. Hand protection: ---

8.5. Respiratory protection: ---

9. Physical and chemical properties

9.1. Appearance, colour, odour: yellow oily liquid

9.2. Boiling point/range: ---

9.3. Flash point: ---

9.4. Inflammability: 350 °C

9.5. Explosion limits:---

9.6. Density: 0,93 kg/l

9.7. Vapour pressure: ---

9.8. Water solubility: insoluble

9.9. Fat solubility: ---

10. Stability and reactivity:

10.1. If the oil is infiltrated into porous material: Danger of self-ignition.

11. Health

11.2 acute toxic: ---

11.3 irritating, corrosive: If the person is sensitive, it may cause skin irritation.

11.4 allergy: ---

11.5 inhalation : ---.

12.Environment

12.1 Biodegradable

13.Waste management

13.1 Collect all waste and destroy according to waste management program. Rags and paper which have adjoined with the product can SELF IGNITE and should be dealt with accordingly, e.g. storing in the water or by burning them.

13.2 Empty and dry packages can be taken into the waste or disposed according to local legislation.

14.Transport

UN number ---

Land : III, class: ---

Sea (IMDG) : ---

15.Regulatory information

Labelling: Xi - irritative

R -PHRASES

S – PHRASES

16.Other information

16.1Uses or/and applications: wood care

16.2Exact operating instruction is on the label and on product instruction

Information: Amello Group OÜ +372 6 720 471